

Defender RiserGuard

Discreet yet smart, RiserGuard is the perfect solution to protect and secure access to building services and storage areas such as dry riser cupboards.





The Defender RiserGuard has been designed and fire tested for use in riser shafts in larger buildings and provides protection to riser openings, preventing fire escaping throughout multi-storey buildings.

Manufactured from steel with riveted and welded frame corners that are concealed. The Defender RiserGuard is available with a standard beaded frame and has an insulated and strengthened core providing a two hour fire rating.

Hardware

A quick release heavy duty pivot hinge is welded into the door trays with a concealed escutcheon plus a five point euro-profile lock is fitted as standard.

Acoustic Rating

Available to a maximum reduction of 47 dB Rw.

Air Tightness

Thermally insulated and air-sealed options are available to 0.5 m/m/h leakage.

Structural opening sizes (mm)

	Min width	Max width	Min height	Max height
Single Door	370	925	765	2866
Single Door	370	1066	765	2488
Double Door	790	1800	765	2866

Available Extras

A range of optional extras are available to suit your project requirements. These include: picture framed, manufactured from stainless steel, double, triple or quadruple solutions available. Contact us with your specific requirements to see how we can help.

Features at a glance

Fire rated FD120S

Insulated core

Manufactured from steel

Quick release pivot hinge

5 point Euro Profile lock

Concealed frame

Available primed for onsite painting or fully finished in any standard RAL colour.





