











Metabor









The Defender Safeguard is our flagship bespoke steel door system—stronger as standard and fully customisable for any application.

Precision-engineered from 1.5mm galvanised steel with a mineral wool core and internal steel reinforcements, it delivers unmatched durability.

Door Leaf

- Anti-jemmy flange on the leading edge (square edged option available)
- 1.5mm galvanised steel (upgrades:
 2.0mm galvanised or 1.5mm
 stainless steel, 304/316)
- Weld-free construction prevents premature failure
- Mineral wool core with internal strengtheners (chipboard upgrade for added strength).

Frames

- 90mm single rebate frame in 2.0mm galvanised steel (stainless option available)
- Custom dimensions and alternative profiles (double rebated, face-fixed, ModuleX integral cloaking and more)
- Bolted corners for strength
- Threaded adjustors for easy installation (16+ fixings). Optional plain fixing plates
- 3mm steel hinge brackets
- Insulated frames available.

Thresholds

- Standard DDA-compliant chamfered profile in 2mm stainless steel
- Options: raised/extended cills, inward-opening profiles with drainage, 4mm ramped design
- Integrated removable thresholds available.

Seals

Tubular silicone rubber seal bonded into frame for optimal weather, thermal, and acoustic performance.

Hardware

- Stainless steel ball bearing hinges (4+ per door, with security dogbolts)
- Hinge upgrade options: concealed bearings, special finishes, fully concealed, heavy-duty continuous hinges
- Extensive hardware range: locks, latches, handles, panic hardware, closers, and stays. Custom hardware integration available.

Thermal Performance

Standard U-value: 2.2 W/m²K (upgradeable to 1.4 W/m²K with Thermaguard Technology).

Acoustic Option

Acoustic rated option available.

Vision Panels & Louvres

- Custom-sized vision panels in rectangular, square, or round styles
- Single, double, or triple glazed options with privacy films, blinds, and obscure glass

Louvres: medium-duty aluminium or heavy-duty steel (150mm to fulldoor).

Over Panels & Side Panels

Designed to expand openings, these panels integrate seamlessly with Defender Safeguard doorsets

- Removable overpanels/transoms: Ideal for periodic access (e.g. large machinery)
- Glazed panels: Single or double glazed with weathertight wedgegasket seals
- Louvred panels: Medium-duty aluminium or heavy-duty steel cassettes (optional insect/rodent mesh).

Finishes

- Powder coated in any RAL colour (marine-grade option available)
- Special finishes: textured, metallic, and woodgrain effects for a premium look.

Structural opening sizes (mm)* Max width Max height Single leaf 1470 3800 Double leaf 2860 3800 *Based on a 33mm wide frame. For oversized doors, please enquire.

