

# METADOR



## Thermaguard Upgrade

# Thermally efficient steel doorsets

The Thermaguard doorset upgrade is independently accredited to provide a U-value as low as 1.4 W/m<sup>2</sup>K for a single doorset.



E [sales@metador.com](mailto:sales@metador.com)

W [metador.com](http://metador.com)

T 01642 337119

# METADOR



Thermally Rated



High Security



Internal or External Use  
Fire Rated



Acoustic



DDA Compliant

The Thermaguard upgrade has been developed to meet the increased demands for energy-efficient buildings as part of a greener future.

A Thermaguard upgraded doorset uses a range of design innovations that reduce the U-value of a typical single doorset to as low as 1.4 W/m<sup>2</sup>K, meeting the latest requirements of the Building Regulations Part L in England, Scotland and Wales. These doorsets are accredited by a UKAS approved company as defined by the requirements of BS EN 10077-2:2017.

## Door Leaf

- Anti-jemmy flange on the leading edge (square edged option available)
- 1.5mm galvanised steel
- Weld-free construction prevents premature failure
- Mineral wool core with internal strengtheners
- 60mm depth minimum door leaf to achieve a U-value of 1.5 W/m<sup>2</sup>K
- 70mm depth minimum door leaf to achieve a U-value of 1.4 W/m<sup>2</sup>K.

## Frames

- 110mm depth minimum door frame to achieve a U-value of 1.5 W/m<sup>2</sup>K
- 120mm depth minimum door frame to achieve a U-value of 1.4 W/m<sup>2</sup>K
- Bolted corners for strength
- Threaded adjustors for easy installation (16+ fixings). Optional plain fixing plates
- 3mm steel hinge brackets.

## Thresholds

- Standard DDA-compliant chamfered profile in 2mm stainless steel
- Options: raised/extended cills, inward-opening profiles with drainage, 4mm ramped design
- Thresholds available fixed or removable.

## Seals

Tubular silicone rubber seal bonded into frame for optimal weather, thermal, and acoustic performance.

## Hardware

- Stainless steel ball bearing hinges (4+ per door, with security dogbolts)
- Upgrade options: concealed bearings, special finishes, fully concealed, heavy-duty continuous hinges
- Extensive hardware range: locks, latches, handles, panic hardware, closers, and stays. Custom hardware integration available.

## Fire Rated Option

Fire ratings for internal or external use up to 120mins are available with this doorset upgrade.



## Thermal Performance

1.5 W/m<sup>2</sup>K or 1.4 W/m<sup>2</sup>K values achievable with this doorset, dependent on requirements.

## Acoustic Option

Acoustic rated option available.

## Vision Panels

- Custom-sized vision panels to meet requirements
- Triple glazed options with privacy films, obscure or patterned glass.

## Over Panels & Side Panels

- Removable overpanels/transoms: Ideal for periodic access (e.g. large machinery)
- Glazed panels: Triple glazed with weathertight wedge-gasket seals.

## Finishes

- Powder coated in any RAL colour (marine-grade option available)
- Special finishes: textured, metallic, and woodgrain effects for a premium look.

